

# Exit Button

## CAZK920 / 922



- Non touch/Touch free Exit Sensor (Diffused Detection)
- Dimensions: 115 x 70 x 25 mm
- Input Voltage: 12VDC
- Contact rating: 12-28V @ 3A
- Contacts : NO, NC, COM
- Mechanical life: 100.000 tests
- Operating temperature: -20 °C ~ 55 °C
- Operating humidity: 0-95%
- Detection range: 1 - 15 cm
- Weight: 0,15kg

## CAZK900 / 905



- Implemented as toggle switch with auto-reset
- Popular model (recognizable)
- Robust design in pale-white ABS housing
- Key symbol printed on key
- Shielded contacts
- Tested at 500,000 cycles
- Potential-free changeover relay N / O and N / C
- CAZK900 : Flush Mount version
- Dimensions : 86 x 86 x 20 mm
- CAZK905 : Surface Mount version
- Dimensions : 86 x 86 x 20 mm

## CAZK925



- Design exit button
- Comes with back plate mounting
- Surface mount
- Change-over contact
- Dual led indication
- Power supply: 12 – 24 VDC
- Dimensions: 86 x 86 x 20 mm
- Output contact: Relay NO, NC, COM 12-28V @ 3A
- Lifespan: 500.000 times
- Detection range: 3 mm
- LED indicator: blue in standby, green when activated
- Operating humidity: 0 – 95 %
- Operating temperature: -20°C – 55°C, IP54
- Weight: 0,12 kg

## CAZK930



- Exit button casted in zinc alloy
- Comes with back box mounting
- Suitable for hollow doors
- Elegant and timeless design
- Change-over contact
- Dimensions: 53 x 53 x 26 mm
- Current: 3A @ 36VDC Max
- Output contact: NO, NC, COM
- Mechanical life: tested up to 100.000 times
- Standard structure: zinc alloy plate, steel button
- Panel material: alloy panel, draw bench finished
- Operating temperature: 10 °C – 55°C
- Operating humidity: 0 – 95 %