

## DS-D6065UN

### Wall-mounted Digital Signage



- Plastic shell appearance, slim frame, and all-in-one design.
- Exquisite image, auto-coloring and image-enhancing engine.
- Variable materials, static and dynamic materials, including the pictures, audio, video, scrolling subtitle, PDF, webpages, live video, number calling, pop-up pictures, etc.
- Flexible program schedule, free schedules and district play of multiple materials and variable play modes: play by day, play by week, play by loop, custom play, etc.
- Centralized management, remotely control and manage one screen or more screens, such as timed startup/shutdown, quick startup/shutdown, brightness/volume timed adjustment, and screenshot preview, remotely release programs and updates local (USB) programs.
- Organization permission, 5-level organization is available for managing materials, programs, terminals, and users, and support creating custom users, allocating permission for users according to user level, and permission templates.
- Multiple security safeguards, 3-level check of materials, programs and schedules to prevent mistake release, encryption of data in storage and transmission to prevent data tampering, and with no default password, users can activate and set initial password to guarantee the password safety.



## • Specification


| Model                  |                             | DS-D6065UN                                                                                                                                                                   |
|------------------------|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Display                | Viewing Angle               | 178°(H) /178°(V)                                                                                                                                                             |
|                        | Contrast Ratio              | 1200:1                                                                                                                                                                       |
|                        | Screen Size                 | 65 inch                                                                                                                                                                      |
|                        | Active Display Area         | 1428.48(H) × 803.52(V) mm                                                                                                                                                    |
|                        | Backlight                   | DLED                                                                                                                                                                         |
|                        | Pixel Pitch                 | 0.372 (H) × 0.372 (V) mm                                                                                                                                                     |
|                        | Resolution                  | 3840 × 2160                                                                                                                                                                  |
|                        | Brightness                  | 500 cd/m <sup>2</sup>                                                                                                                                                        |
|                        | Color Depth                 | 1.07G(8 Bits+FRC)                                                                                                                                                            |
|                        | Response Time               | 8 ms                                                                                                                                                                         |
|                        | Color Gamut                 | 72% NTSC                                                                                                                                                                     |
|                        | Reliability                 | 7 × 24 H                                                                                                                                                                     |
|                        | Refresh Rate                | 60 Hz                                                                                                                                                                        |
| Built-in System        | Operation System            | Android 8.0                                                                                                                                                                  |
|                        | Processor                   | A73*2+A53*2, 1.7GHz                                                                                                                                                          |
|                        | Memory                      | 3 GB                                                                                                                                                                         |
|                        | Built-in Storage            | 32 GB                                                                                                                                                                        |
| Interface              | Video & Audio Input         | DVI-I × 1, HDMI2.0 × 2, DP1.2 × 1, Audio line in × 1                                                                                                                         |
|                        | Video & Audio Output        | DP1.2 × 1, Audio line out × 1                                                                                                                                                |
|                        | Network Interface           | LAN × 1, Wi-Fi × 1                                                                                                                                                           |
|                        | Data Transmission Interface | USB 2.0 × 2, TF Card × 1                                                                                                                                                     |
| Processing Performance | Decode Capacity             | Support 1 channel multimedia video (4K); support decoding 2 MP video stream.                                                                                                 |
| Internal Function      | Loudspeaker                 | Built-in speaker (10 W) × 2                                                                                                                                                  |
| Working Environment    | Storage Temperature         | -20 °C to 60 °C (-4 °F to 104 °F)                                                                                                                                            |
|                        | Storage Humidity            | 10% to 90% RH                                                                                                                                                                |
| General                | Material Type               | DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, TS, FLV, WEBM, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF, MXMF, RTTTL, RTX, OTA, IMY, JPG, JPEG, BMP, GIF, PNG |
|                        | Power Supply                | AC 100V-240V                                                                                                                                                                 |
|                        | Power Consumption           | 179W+/- 10%(TYP), 330W(MAX)                                                                                                                                                  |
|                        | Standby Consumption         | ≤ 0.5 W                                                                                                                                                                      |
|                        | Working temperature         | 0 °C to 40 °C (32 °F to 104 °F)                                                                                                                                              |
|                        | Working humidity            | 20% to 80% RH                                                                                                                                                                |


|  |                                   |                                                        |
|--|-----------------------------------|--------------------------------------------------------|
|  | Product Dimensions<br>(W × H × D) | 1462.3 × 837.3 × 93.4 mm                               |
|  | Package Dimensions<br>(W × H × D) | 1616 × 998 × 187 mm                                    |
|  | Net weight                        | 27.8 kg                                                |
|  | Gross weight                      | 36.8 kg                                                |
|  | Packing List                      | power cord, remote control, user manual, warranty card |

## ▪ Available Model

DS-D6065UN

## ▪ Dimension





Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216) 521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-97-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-[0]31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com