

A modified Specification

(AC5000)

1. The reason for modifying
 - Function for connecting SR100 is added and fingerprint capture routine is changed when setting SFD.
 - Firmware is modified to apply New LCD.

2. Modifying
 - As authorizing using card, fingers press keypad on terminal.
 - ➔ In case that it is detected that more than 10 keys are pressed, keypad is enable.
 - It doesn't allow user who registers FPCard to modify.
 - As setting wiegand bypass, if authentication using FP, card number can be sent.
 - Dutch and French are added.
 - New LCD can be applied (as new LCD is applied to board, HW version is 20.)
 - If sendfail=3 on WiegandOut, as authentication using card is failed, card data is sent.
 - Flash storage speed is improved.
 - As FDB error occurs, if user is downloaded, error (5009) is responded.
As entering the administration management menu, error message is displayed.
 - Blacklist message is added.
 - As setting Wiegand In, 2&3(LSByte)is added to ByteOrder.
 - Function for setting External Device is added.
(1=Wiegand CardReader, 2=SR100 on menu->5.Terminal->6.ExternalDevice)
 - Function for setting calendar is added.
(Persian calendar is added on menu->4.System->5.DateTime)
 - Fingerprint capture routine is modified.
 - Uploading logs periodically is added.
 - As more than 100byte for notice, it is modified that the problem about retting terminal.
 - 5.Hexa_1 is added on menu -> 5.Terminal -> 5.Card Reader -> CardFormat. (6byte Hexa is displayed on 125K.)

3. Firmware version : ac5k_ex_small_10.51.03-000.07(e790c0cd)_20120801.bin